



THE CITY OF  
**Red Deer**

**Traffic Section  
Engineering Services Department**

# **Temporary Traffic Control Manual**

## Foreword

This manual provides guidance for planning and implementing temporary traffic control for work within the City of Red Deer Right-of-Way (ROW).

It is to be used in conjunction with the *Manual of Uniform Traffic Control Devices for Canada* (MUTCDC) and incorporates practices tailored to Red Deer's transportation network.

The purpose of this manual is to ensure that temporary traffic accommodation is applied consistently and effectively to promote the safety of workers, pedestrians, cyclists, and motorists.

All personnel responsible for traffic control within the City ROW are encouraged to use this manual as a reference for planning and implementing safe and effective traffic control measures.



**Kyle Perron, P.Eng.**

Traffic Operations Engineer



2025-09-16

## Contents

Introduction .....	5
Use of Streets Permit .....	5
Traffic Accommodation Strategy (TAS) .....	5
Temporary Traffic Control Zone Components .....	6
Traffic Control Devices .....	7
Spacing Requirements .....	7
Taper Types .....	8
Tangent Types .....	8
 Drawing Index	
1.0 Components and Tapers	
1.1 Components of a Temporary Traffic Control Zone .....	9
1.2 Taper Types .....	10
2.0 Roadside Work	
2.1 Roadside Work .....	11
2.2 Work Adjacent to a Roadway .....	12
2.3 Shoulder Work .....	13
2.4 Work on Edge of Roadway .....	14
2.5 Bike Lane Closure .....	15
3.0 Single Lane Closures	
3.1 Yield to Oncoming Traffic .....	16
3.2 Single Right Lane Closure .....	17
3.3 Single Left Lane Closure .....	18
3.4 Work in the Inner Lane of a Two-Lane Roundabout .....	19
4.0 Multi-Lane Closures	
4.1 Multi-Lane Closure Two Right Lanes .....	20
4.2 Multi-Lane Closure Two Left Lanes .....	21
4.3 Multi-Lane Closure Left Lane Closed in Each Direction .....	22
5.0 Crossovers	
5.1 Centre Line Crossover Two-Way Traffic .....	23
5.2 Median Crossover Two-Way Traffic .....	24

**6.0 Intersections**

6.1 Intersection Work – Example 1 .....	25
6.2 Intersection Work – Example 2 .....	26
6.3 Intersection Work – Example 3 .....	27
6.4 Intersection Work – Example 4 .....	28
6.5 Intersection Work – Example 5 .....	29
6.6 Intersection Work – Example 6 .....	30
6.7 Intersection Work – Example 7 .....	31
6.8 Intersection Work – Example 8 .....	32

**7.0 Road Closures**

7.1 Back Lane Closure .....	33
7.2 Road Closure .....	34
7.3 Cul-De-Sac Closure.....	35

**8.0 Sidewalks**

8.1 Sidewalk Closure – Midblock (Active Site) .....	36
8.2 Sidewalk Closure – Midblock (Idle Site).....	37
8.3 Sidewalk Closure – Intersection Corner (Active Site).....	38
8.4 Sidewalk Closure – Intersection Corner (Idle Site).....	39
8.5 Sidewalk Work – Right Lane Closure.....	40
8.6 Sidewalk Work – Partial Sidewalk Closure.....	41

**9.0 Mobiles**

9.1 Moving Jobs .....	42
9.2 Mobile Operations – Roadside Work and Shoulder Work .....	43
9.3 Mobile Operations on Residential .....	44
9.4 Mobile Operations on Collector or Arterial $V \leq 60 \text{ km/h}$ .....	45
9.5 Mobile Operations on Arterial $V \geq 70 \text{ km/h}$ .....	46

References .....	47
------------------	----

## Introduction

The TEMPORARY TRAFFIC CONTROL MANUAL has been developed to assist with preparing a Traffic Accommodation Strategy (TAS) for review and approval by The City of Red Deer. It establishes standardized temporary traffic control requirements to ensure the safety of all road users, pedestrians, workers, and equipment in and around work zones within the City's Right-of-Way (ROW). This manual serves as a reference for contractors, consultants, utility companies, and City staff involved in temporary traffic control operations.

## Use of Streets Permit

A Use of Streets Permit is required for work within the City's ROW. This permit consists of temporary Parking Stall Reservation, Street/Lane/Sidewalk Closure, Lot Parking Stall Reservation, and/or Property Owner Requests within City owned Parking Lots for a defined date range at a specific address/location.

For more information on the Use of Streets Permit, visit:

<https://www.reddeer.ca/city-services/permits-and-inspections/use-of-streets--windrow-removal-permits/>

To complete the Use of Streets Permit Application, visit:

<https://www.reddeer.ca/media/reddeerca/city-services/engineering/Use-of-Streets-Permit-Application.pdf>

Applicants can obtain approval for this permit by submitting it to Engineering Services at [engineering@reddeer.ca](mailto:engineering@reddeer.ca) or by calling 403-342-8158 if assistance is required. A minimum of two business days prior notice is required for processing and coordination of these requests.

## Traffic Accommodation Strategy (TAS)

A TAS is required for all Street/Lane/Sidewalk Closures within the City's ROW. Applicants must submit a TAS to Engineering Services with a minimum of 2-3 business days' notice for review and approval prior to the closure.

The TAS must include, at minimum:

- Site Map/Drawing/Diagram: Clearly indicating the location, extent of the closure, and the work space.
- Traffic Control Devices: Placement of signs, delineation devices, barriers, arrow boards, etc.
- Flag Persons: Locations of flaggers, if required.
- Site Contact Information: Name and cell phone number of the site contact.

The TAS should be prepared by following the examples provided in this manual. Elements from multiple examples may be combined or adapted as applicable to best suit situational conditions. If a particular closure is not included in this manual, applicants should refer to the *Manual of Uniform Traffic Control Devices for Canada* (MUTCDC), Sixth Edition, for appropriate guidance. If approved, a road closure notification will be sent to Parks & Public Works to communicate the closure to the public and a Use of Streets Permit will be issued to the applicant.

Alternatively, applicants can request traffic control through [parksandpublicworks@reddeer.ca](mailto:parksandpublicworks@reddeer.ca). This option also requires a minimum of 2-3 business days' notice prior to the closure to confirm crew availability. If approved, the applicant will need to complete a work order confirming the details of their request. From the completed work order, Engineering Services will issue a Use of Streets Permit to the applicant. Please note that Parks and Public Works charge additional fees for their traffic control separate from the Use of Streets Permit.

## Temporary Traffic Control Zone Components

A temporary traffic control zone extends from the first advance warning sign to the last traffic control device which returns vehicles to normal road conditions. The temporary traffic control zone is divided into four components:

### 1. Advance Warning Area

This area informs drivers to expect work ahead and any necessary actions to take. The number and type of traffic control devices in this area must account for downstream conditions, such as reduced speeds or lane closures. Devices should be spaced appropriately to provide drivers with sufficient reaction time to interpret the information and react before reaching the work area.

### 2. Transition Area

This area moves traffic out of the normal path to accommodate situations such as lane closures or shoulder work that may encroach into adjacent travel lanes. Delineation devices should clearly define the intended path, ensuring drivers do not follow the wrong direction. This area must be free of parked vehicles, equipment, or material storage.

### 3. Activity Area

This area is where the work occurs and includes the longitudinal buffer space, lateral buffer space, work space, and traffic space.

- Longitudinal buffer space: Provides protection for traffic and workers, acting as a recovery zone for errant vehicles. This space should remain free of parked vehicles, equipment, or material storage.
- Lateral buffer space: Provides protection for traffic and workers, separating the traffic space from the work space. Engineering judgment should determine its width while considering factors such as speed, traffic volume, lane width, vehicle class, time of day, and work duration.
- Work space: Area set aside for workers, equipment, and material storage. Measures should be taken to minimize hazards and distractions for both road users and workers.
- Traffic space: Allows traffic to pass through the activity area. Minimum lane widths of 3.3 metres shall be maintained for emergency vehicles.

### 4. Termination Area


This area lets traffic resume normal driving. It extends from the end of the work space to the point where traffic returns to normal road conditions.

## Traffic Control Devices

All temporary traffic control devices – including signs, delineation devices, barricades, flashers, arrow boards, and variable message boards – should comply with the MUTCD, Sixth Edition.

Equivalent signage not illustrated in this manual is acceptable, provided it conveys the same message to road users clearly and effectively. Any such signage must adhere to MUTCD standards with respect to size, shape, and colour.

Signage equivalency examples:



## Spacing Requirements

The spacing of traffic control devices is determined by the posted speed limit. Proper spacing allows sufficient driver reaction time and provides clear direction for road users while maintaining safety for workers. See Table 1.

Table 1: Spacing Requirements

V (km/h)	A (m)	L (m)	B (m)	D (m)	R (m)	N
30	25	10	20	6	30	5
50	50	30	35	8	40	5
60	50	40	45	12	50	5
70	75	60	50	15	65	8

Where:

**V** = Speed limit

**A** = Spacing between signs

**L** = Length of taper

**B** = Length of longitudinal buffer space

**D** = Spacing between delineation devices

**R** = Run-in-length on centre line

**N** = Number of delineation devices per taper

**Note:** Spacing and taper lengths may vary based on situational conditions, such as road geometry and space limitations.

## Taper Types

Table 2: Taper Types


TAPERS		
TYPE	DESCRIPTION	LENGTH
<b>Merging taper</b>	A lane closure taper used to merge traffic from a closing travel lane into an adjacent travel lane.	L (min)
<b>Shifting taper</b>	Used when a travel lane is shifted laterally by up to one lane width. Drivers follow a path of travel without merging or diverging.	L/2 (min)
<b>Shoulder taper</b>	Closes a shoulder to create a work space or storage area. May be used for full-time parking lanes. For part-time parking lanes, consider a merging taper if necessary.	L/3 (min)
<b>Two-way taper</b>	Closes a travel lane on a two-way roadway while allowing alternating traffic in each direction.	10 m – 30 m
<b>Downstream taper</b>	Provides a transition from the activity area back to the normal path of travel.	L/3 (min)

## Tangent Types

Table 3: Tangent Types


TANGENTS		
TYPE	DESCRIPTION	LENGTH
<b>Merge followed by merge</b>	The parallel distance between the end of one merge taper and the start of another. A minimum of one merge taper length is required; twice the length is recommended for high-speed or high-volume roads.	L (min), 2L (desired)
<b>Merge followed by shifting taper</b>	The parallel distance between the end of a merge taper and the start of a shifting taper. A minimum of one merge taper length should be provided to allow drivers time to react to traffic control devices.	L (min)
<b>Buffer</b>	Provides a recovery area for errant vehicles, separating work zones from traffic or opposing traffic lanes.	B
<b>Run-in-length on centreline</b>	A tangent length used before a lane shift or the end of a merge on the centreline.	R

## 1.1 Components of a Temporary Traffic Control Zone




		THE CITY OF RED DEER		ENGINEERING DEPARTMENT	
DRAWN BY:	G.B.	TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:	
DATE:	JAN. 2025				
SCALE:	N.T.S.	COMPONENTS OF A TEMPORARY TRAFFIC CONTROL ZONE		ENGINEER	
NO.	DATE	REVISION		DRAWING NO.	1.1

## 1.2 Taper Types



		THE CITY OF RED DEER      ENGINEERING DEPARTMENT	
		DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL
		DATE: JAN. 2025	TAPER TYPES
		SCALE: N.T.S.	
NO.	DATE	REVISION	DRAWING NO. 1.2

## 2.1 Roadside Work




### ROADSIDE WORK

1. EXAMPLE SHOWN:  
Two-lane - two-way road without shoulder.  
No encroachment onto road.
2. CONDITIONS:  
Work site must be in the boulevard area, completely off the road.  
Excavations require protection.
3. NOTES:  
Note use of advance warning sign.
4. Set-up procedure  
Set up advance warning sign and then delineation devices.  
Use rotating light & flashers on equipment.  
Commence work.


			THE CITY OF RED DEER	ENGINEERING DEPARTMENT	
			DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL	APPROVED BY:
			DATE: JAN. 2025	ROADSIDE WORK	ENGINEER
NO.	DATE	REVISION	SCALE: N.T.S.		DRAWING NO. 2.1

## 2.2 Work Adjacent to a Roadway



		THE CITY OF RED DEER		ENGINEERING DEPARTMENT	
DRAWN BY:	G.B.	TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:	
DATE:	JAN. 2025	WORK ADJACENT TO A ROADWAY		ENGINEER	
SCALE:	N.T.S.			DRAWING NO.	2.2
NO.	DATE	REVISION			


## 2.3 Shoulder Work



\* Sign is optional if an arrow board is being used.


			THE CITY OF RED DEER      ENGINEERING DEPARTMENT			
			DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL	APPROVED BY:	
			DATE: JAN. 2025	SHOULDER WORK		ENGINEER
NO.	DATE	REVISION	SCALE: N.T.S.			DRAWING NO. 2.3

## 2.4 Work on Edge of Roadway




			THE CITY OF RED DEER      ENGINEERING DEPARTMENT		APPROVED BY: ENGINEER DRAWING NO. <b>2.4</b>	
			DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL		
			DATE: JAN. 2025	WORK ON EDGE OF ROADWAY		
			SCALE: N.T.S.			
NO.	DATE	REVISION				

## 2.5 Bike Lane Closure




THE CITY OF RED DEER ENGINEERING DEPARTMENT		
DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL	APPROVED BY:
DATE: JAN. 2025		ENGINEER
SCALE: N.T.S.	BIKE LANE CLOSURE	DRAWING NO. 2.5
NO. DATE	REVISION	

## 3.1 Yield to Oncoming Traffic



			THE CITY OF RED DEER      ENGINEERING DEPARTMENT		
			DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL	APPROVED BY:
			DATE: JAN. 2025	YIELD TO ONCOMING TRAFFIC	
			SCALE: N.T.S.		
NO.	DATE	REVISION			ENGINEER DRAWING NO. <b>3.1</b>


## 3.2 Single Right Lane Closure



\* Sign is optional if an arrow board is being used.

THE CITY OF RED DEER ENGINEERING DEPARTMENT		
DRAWN BY: G.B.		TEMPORARY TRAFFIC CONTROL MANUAL
DATE: JAN. 2025		SINGLE RIGHT LANE CLOSURE
SCALE: N.T.S.		
NO. DATE	REVISION	APPROVED BY:  ENGINEER DRAWING NO. <b>3.2</b>


### 3.3 Single Left Lane Closure



\* Sign is optional if an arrow board is being used.


			<b>THE CITY OF RED DEER      ENGINEERING DEPARTMENT</b>		
			<b>DRAWN BY:</b> G.B.	<b>TEMPORARY TRAFFIC CONTROL MANUAL</b>	<b>APPROVED BY:</b>
			<b>DATE:</b> JAN. 2025	<b>SINGLE LEFT LANE CLOSURE</b>	<b>ENGINEER</b>
			<b>SCALE:</b> N.T.S.		<b>DRAWING NO.</b>
NO.	DATE	REVISION			3.3

### 3.4 Work in the Inner Lane of a Two-Lane Roundabout




			THE CITY OF RED DEER		ENGINEERING DEPARTMENT	
DRAWN BY:	G.B.		TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:	
DATE:	JAN. 2025		WORK IN THE INNER LANE OF A TWO-LANE ROUNABOUT		ENGINEER	
SCALE:	N.T.S.				DRAWING NO.	3.4
NO.	DATE	REVISION				

## 4.1 Multi-Lane Closure Two Right Lanes



THE CITY OF RED DEER ENGINEERING DEPARTMENT		
DRAWN BY: G.B.		TEMPORARY TRAFFIC CONTROL MANUAL
DATE: JAN. 2025		MULTI-LANE CLOSURE TWO RIGHT LANES
SCALE: N.T.S.		
NO.	DATE	REVISION


## 4.2 Multi-Lane Closure Two Left Lanes



\* Sign is optional if an arrow board is being used.


		THE CITY OF RED DEER      ENGINEERING DEPARTMENT		
		DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL	APPROVED BY:
		DATE: JAN. 2025	MULTI-LANE CLOSURE TWO LEFT LANES	
		SCALE: N.T.S.		
NO.	DATE	REVISION		ENGINEER DRAWING NO. <b>4.2</b>

## 4.3 Multi-Lane Closure Left Lane Closed in Each Direction




		THE CITY OF RED DEER      ENGINEERING DEPARTMENT	
		DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL
		DATE: JAN. 2025	MULTI-LANE CLOSURE LEFT LANE CLOSED IN EACH DIRECTION
		SCALE: N.T.S.	
NO.	DATE	REVISION	

## 5.1 Centre Line Crossover Two-Way Traffic



			THE CITY OF RED DEER      ENGINEERING DEPARTMENT			
			DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:
			DATE: JAN. 2025	CENTRE LINE CROSSOVER TWO-WAY TRAFFIC		ENGINEER
			SCALE: N.T.S.			DRAWING NO. 5.1
NO.	DATE	REVISION				

## 5.2 Median Crossover Two-Way Traffic



			THE CITY OF RED DEER		ENGINEERING DEPARTMENT	
DRAWN BY:	G.B.		TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:	
DATE:	JAN. 2025		MEDIAN CROSSOVER TWO-WAY TRAFFIC		ENGINEER DRAWING NO.	
SCALE:	N.T.S.					
NO.	DATE	REVISION				5.2

## 6.1 Intersection Work – Example 1

### INTERSECTION WORK - EXAMPLE 1

#### 1. EXAMPLE SHOWN:

Two-lane - four-legged intersection.

#### 2. CONDITIONS:


Require a portion of each lane in each direction.

#### 3. NOTES:

Use traffic control persons to protect workers during set-up.  
Use No Left Turn signs where applicable. Confirm vehicle turn path.

#### 4. SET-UP PROCEDURE:

Set up all advance warning signs first.  
Outline work site with delineation devices and Lane Closure Arrow signs.  
Commence work.



			THE CITY OF RED DEER ENGINEERING DEPARTMENT			
DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY: ENGINEER			
DATE: JAN. 2025			DRAWING NO. 6.1			
SCALE: N.T.S.	INTERSECTION WORK EXAMPLE 1					
NO. DATE	REVISION					

## 6.2 Intersection Work – Example 2

### INTERSECTION WORK - EXAMPLE 2

#### 1. EXAMPLE SHOWN:

Four-legged intersection. Two approaching lanes in all directions.

#### 2. CONDITIONS:


Single-lane closure in all directions.

#### 3. NOTES:

Use traffic control persons to protect workers during set-up.  
May require left turn prohibitions. Consult Traffic Section.  
Ensure lane closures are in place before reaching intersection.  
Arrow board may replace barricade where shown.


#### 4. SET-UP PROCEDURE:

Set up advance warning signs and tapers for each direction. Start from edges of diagram and progress toward the work site as shown.  
Outline work site with delineation devices.  
Commence work.



			THE CITY OF RED DEER		ENGINEERING DEPARTMENT	
			DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:  ENGINEER DRAWING NO.
			DATE: JAN. 2025	INTERSECTION WORK EXAMPLE 2		
NO.	DATE	REVISION	SCALE: N.T.S.			6.2

## 6.3 Intersection Work – Example 3



			THE CITY OF RED DEER		ENGINEERING DEPARTMENT	
			DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:
			DATE: JAN. 2025	INTERSECTION WORK EXAMPLE 3		ENGINEER
			SCALE: N.T.S.			DRAWING NO. 6.3
NO.	DATE	REVISION				

## 6.4 Intersection Work – Example 4

### INTERSECTION WORK - EXAMPLE 4

#### 1. EXAMPLE SHOWN:

Four-legged intersection. Two approaching lanes in all directions.

#### 2. CONDITIONS:


Single mandatory left-lane condition.  
Single mandatory right-lane condition.

#### 3. NOTES:

Use traffic control persons to protect workers during set-up.  
Mandatory left and right lanes may require closure depending on traffic volume.  
Note Sidewalk Closed and Pedestrian Detour signs.

#### 4. SET-UP PROCEDURE:

Set up advance warning sign and mandatory left-lane condition signs in order shown at top of diagram.  
Set up advance warning sign and mandatory right-lane condition signs in order shown at left side of diagram.  
Outline work site with delineation devices and barricades.  
Commence work.



			THE CITY OF RED DEER      ENGINEERING DEPARTMENT			
DRAWN BY:	G.B.		TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:	
DATE:	JAN. 2025		INTERSECTION WORK EXAMPLE 4			ENGINEER
SCALE:	N.T.S.					DRAWING NO.
NO.	DATE	REVISION				6.4

## 6.5 Intersection Work – Example 5

## INTERSECTION WORK - EXAMPLE 5

## 1. EXAMPLE SHOWN:

Four-legged intersection. Two approaching lanes in all directions.

## 2. CONDITIONS:

Two lanes closed in one direction.

Single-lane closure in opposing direction.

## 3. NOTES:

Use traffic control persons to protect workers during set-up.  
May require left turn prohibition. Mandatory right lane may require closure depending on traffic volume.

Arrow board may replace barricade where shown.

Note Sidewalk Closed and Pedestrian Detour signs.

## 4. SET-UP PROCEDURE:


Start at the bottom and right side of the diagram. Set up single-lane closure as shown except for delineation devices and signs in intersection.

Set up mandatory right-lane condition and Two-Way Traffic signs to top right of diagram.

Start at top of diagram. Set up double-lane closure as shown.

Set up delineation devices and signs in intersection.

Commence work.




			THE CITY OF RED DEER ENGINEERING DEPARTMENT			
			DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL	APPROVED BY:	
			DATE: JAN. 2025	INTERSECTION WORK EXAMPLE 5		DRAWING NO. 6.5
NO.	DATE	REVISION	SCALE: N.T.S.			

## 6.6 Intersection Work – Example 6

### INTERSECTION WORK - EXAMPLE 6

#### 1. EXAMPLE SHOWN:

Four-legged intersection. Two approaching lanes in all directions.



#### 2. CONDITIONS:

Two-lanes closed in one direction.

Single-lane closed in two directions.

#### 3. NOTES:

Use traffic control persons to protect workers during set-up.

Arrow board may be used where shown.

Mandatory right lane may require closure depending on traffic volume.

Note Sidewalk Closed and Pedestrian Detour signs.

#### 4. SET-UP PROCEDURE:


Start at the top left of the diagram. Set up mandatory right lane condition signs as shown.

Start at the bottom and the left side of the diagram. Set up single-lane closures and Two-Way Traffic signs as shown. Set up delineation devices and signs in intersection.

Commence work.


			THE CITY OF RED DEER		ENGINEERING DEPARTMENT		
			DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:  ENGINEER DRAWING NO. <b>6.6</b>	
			DATE: JAN. 2025	INTERSECTION WORK EXAMPLE 6			
NO.	DATE	REVISION	SCALE: N.T.S.				

## 6.7 Intersection Work – Example 7




			THE CITY OF RED DEER		ENGINEERING DEPARTMENT	
DRAWN BY:	G.B.		TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:	
DATE:	JAN. 2025		INTERSECTION WORK EXAMPLE 7		ENGINEER DRAWING NO. 6.7	
SCALE:	N.T.S.					
NO.	DATE	REVISION				

## 6.8 Intersection Work – Example 8




THE CITY OF RED DEER ENGINEERING DEPARTMENT		
DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL	APPROVED BY:
DATE: JAN. 2025	INTERSECTION WORK EXAMPLE 8	ENGINEER
SCALE: N.T.S.		DRAWING NO. <b>6.8</b>
NO.	DATE	REVISION

## 7.1 Back Lane Closure




			THE CITY OF RED DEER      ENGINEERING DEPARTMENT			
DRAWN BY:	G.B.		TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:	
DATE:	JAN. 2025		BACK LANE CLOSURE		ENGINEER	
SCALE:	N.T.S.				DRAWING NO.	7.1
NO.	DATE	REVISION				

## 7.2 Road Closure



## 7.3 Cul-De-Sac Closure



			THE CITY OF RED DEER      ENGINEERING DEPARTMENT			
DRAWN BY:	G.B.		TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:	
DATE:	JAN. 2025				ENGINEER	
SCALE:	N.T.S.		CUL-DE-SAC CLOSURE		DRAWING NO.	
NO.	DATE	REVISION				7.3

## 8.1 Sidewalk Closure – Midblock (Active Site)

### SIDEWALK CLOSURE - MIDBLOCK (ACTIVE SITE)

#### 1. EXAMPLE SHOWN:

Pedestrian detour.

#### 2. CONDITIONS:

Pedestrians must be physically separated from vehicular traffic and the work site.

#### 3. NOTES:

Note barricades to physically separate pedestrians from the work site.


Sidewalk Closed and Pedestrian Detour signs direct pedestrians to alternative sidewalk.

Ensure the alternative sidewalk is open to pedestrians for the duration of the sidewalk closure.

#### 4. SET-UP PROCEDURE:

Set up Sidewalk Closed and Pedestrian Detour signs and barricade work site.

Commence work.



			THE CITY OF RED DEER      ENGINEERING DEPARTMENT			
			DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL	APPROVED BY:	
			DATE: JAN. 2025	SIDEWALK CLOSURE - MIDBLOCK (ACTIVE SITE)		
NO.	DATE	REVISION	SCALE: N.T.S.		ENGINEER	DRAWING NO.
						8.1

## 8.2 Sidewalk Closure – Midblock (Idle Site)

### SIDEWALK CLOSURE - MIDBLOCK (IDLE SITE)

#### 1. EXAMPLE SHOWN:

Pedestrian detour on roadway.

#### 2. CONDITIONS:

Pedestrians must be physically separated from vehicular traffic and the work site.

#### 3. NOTES:

Note barricades to physically separate pedestrians from the work site.

Curb ramps from the sidewalk to the roadway are required for wheelchair access.


Pedestrian Detour signs guide pedestrians around the work site.

#### 4. SET-UP PROCEDURE:

Set up advance warning signs.

Set up delineation devices, Pedestrian Detour signs, and barricade work site.

Commence work.



			THE CITY OF RED DEER      ENGINEERING DEPARTMENT			
DRAWN BY:	G.B.		TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:	
DATE:	JAN. 2025		SIDEWALK CLOSURE - MIDBLOCK (IDLE SITE)		ENGINEER	
SCALE:	N.T.S.				DRAWING NO.	
NO.	DATE	REVISION				8.2

### 8.3 Sidewalk Closure – Intersection Corner (Active Site)

**SIDEWALK WORK - INTERSECTION CORNER (ACTIVE SITE)****1. EXAMPLE SHOWN:**

Four-legged intersection with sidewalks. Two approaching lanes in all directions.

**2. CONDITIONS:**

Pedestrians must be physically separated from the work site.


**3. NOTES:**

Note barricades to physically separate pedestrians from the work site. Pedestrian Detour signs direct pedestrians to alternative sidewalk. Ensure the alternative sidewalks are open to pedestrians for the duration of the sidewalk closure.

**4. SET-UP PROCEDURE:**

Set up Pedestrian Detour signs, advance warning signs, Sidewalk Closed signs and barricade work site.

Commence work.



			THE CITY OF RED DEER      ENGINEERING DEPARTMENT			
DRAWN BY:	G.B.		TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:	
DATE:	JAN. 2025		SIDEWALK CLOSURE - INTERSECTION CORNER		ENGINEER	
SCALE:	N.T.S.		(ACTIVE SITE)		DRAWING NO.	
NO.	DATE	REVISION				8.3

## 8.4 Sidewalk Closure – Intersection Corner (Idle Site)

### SIDEWALK WORK - INTERSECTION CORNER (IDLE SITE)

#### 1. EXAMPLE SHOWN:

Four-legged intersection with sidewalks. Two approaching lanes in all directions.

#### 2. CONDITIONS:


Pedestrians must be physically separated from vehicular traffic and the work site.

#### 3. NOTES:

Note barricades to physically separate pedestrians from the work site. Pedestrian Detour signs guide pedestrians around the work site. Delineation devices may be replaced with fencing or other barriers for added safety if needed. Curb ramps from the sidewalk to the roadway are required for wheelchair access.

#### 4. SET-UP PROCEDURE:

Set up advance warning signs at bottom and right side of the diagram as shown. Set up pedestrian detour with curb ramps, delineation devices and/or barriers. Commence work.



			THE CITY OF RED DEER      ENGINEERING DEPARTMENT			
DRAWN BY:	G.B.		TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:	
DATE:	JAN. 2025		SIDEWALK WORK - INTERSECTION CORNER		ENGINEER	
SCALE:	N.T.S.		(IDLE SITE)		DRAWING NO.	
NO.	DATE	REVISION				8.4

## 8.5 Sidewalk Work – Right Lane Closure

### SIDEWALK WORK - RIGHT LANE CLOSURE

#### 1. EXAMPLE SHOWN:

Four-lane - two-way road with sidewalk.

#### 2. CONDITIONS:

Pedestrians must be physically separated from vehicular traffic and the work site.

Pedestrian Detour guides pedestrians into the right lane, closing the right lane to traffic.

Concrete barriers are required to separate pedestrians and vehicles for long-term closures.

#### 3. NOTES:

Note barricades to physically separate pedestrians from the work site.

Delineation devices may be replaced with fencing or other barriers for added safety if needed.


Curb ramps from the sidewalk to the roadway are required for wheelchair access.

#### 4. SET-UP PROCEDURE:

Start at the bottom of diagram. Set up advance warning signs as shown.

Set up taper and pedestrian detour with curb ramps, delineation devices and/or barriers.

Commence work.



\* Sign is optional if an arrow board is being used.

			THE CITY OF RED DEER		ENGINEERING DEPARTMENT	
DRAWN BY:	G.B.		TEMPORARY TRAFFIC CONTROL MANUAL		APPROVED BY:	
DATE:	JAN. 2025		SIDEWALK WORK RIGHT LANE CLOSURE		ENGINEER DRAWING NO.	
SCALE:	N.T.S.					
NO.	DATE	REVISION				8.5

## 8.6 Sidewalk Work – Partial Sidewalk Closure

**SIDEWALK WORK - PARTIAL SIDEWALK  
CLOSURE**

### 1. EXAMPLE SHOWN:

Four-lane - two-way road with sidewalk.

## 2 CONDITIONS

Pedestrians must be physically separated from vehicular traffic and the work site.

Partial sidewalk closure reduces sidewalk width but allows pedestrian access.

### 3. NOTES:

Note barricades to physically separate pedestrians from the work site


pedestrians from the work site. Minimum remaining sidewalk width must be 1.5 metres.

#### 4. SET UP PROCEDURE:



Start at the bottom of diagram. Set up

advance warning signs as shown. Set up taper and outline work site with

### **delineation device**




\* Sign is optional if an arrow board is being used.




		THE CITY OF RED DEER      ENGINEERING DEPARTMENT		
		DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL	APPROVED BY:
		DATE: JAN. 2025	SIDEWALK WORK - PARTIAL SIDEWALK CLOSURE	
		SCALE: N.T.S.		
NO.	DATE	REVISION		DRAWING NO. 8.6

## 9.1 Moving Jobs



		THE CITY OF RED DEER      ENGINEERING DEPARTMENT	
		DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL
		DATE: JAN. 2025	MOVING JOBS
		SCALE: N.T.S.	
NO.	DATE	REVISION	APPROVED BY:  ENGINEER DRAWING NO. <b>9.1</b>

## 9.2 Mobile Operations – Roadside Work and Shoulder Work



### MOBILE OPERATIONS - ROADSIDE WORK AND SHOULDER WORK

#### 1. EXAMPLE SHOWN:

Two-lane, two-way road.

Applicable to multi-lane roads.

#### 2. CONDITIONS:

Work duration: 30 minutes or less. For longer duration work, refer to Drawing No.'s 2.1 - 2.4.

#### 3. NOTES:

Beacon and 4-way flashers or flashing arrow board must be activated to alert traffic of work ahead.


#### 4. SET-UP PROCEDURE:

Activate beacon and 4-way flashers or flashing arrow board to alert traffic of work ahead.

Commence work.

		THE CITY OF RED DEER      ENGINEERING DEPARTMENT	
DRAWN BY:	G.B.	TEMPORARY TRAFFIC CONTROL MANUAL	APPROVED BY:
DATE:	JAN. 2025	MOBILE OPERATIONS - ROADSIDE WORK AND SHOULDER WORK	ENGINEER
SCALE:	N.T.S.		DRAWING NO.
NO.	DATE	REVISION	9.2

### 9.3 Mobile Operations on Residential



#### MOBILE OPERATIONS ON RESIDENTIAL

##### 1. EXAMPLE SHOWN:

Residential road.

##### 2. CONDITIONS:

Work duration: 30 minutes or less.

Must allow 3.3 metres of space for vehicles to pass.

##### 3. NOTES:

Beacon and 4-way flashers or flashing arrow board must be activated to alert traffic of work ahead.

##### 4. SET-UP PROCEDURE:

Activate beacon and 4-way flashers or flashing arrow board to alert traffic of work ahead.

Commence work.

		THE CITY OF RED DEER      ENGINEERING DEPARTMENT	
		DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL
		DATE: JAN. 2025	MOBILE OPERATIONS ON RESIDENTIAL
		SCALE: N.T.S.	
NO.	DATE	REVISION	DRAWING NO. <b>9.3</b>

**9.4 Mobile Operations on Collector or Arterial V ≤ 60 km/h****MOBILE OPERATIONS ON COLLECTOR OR ARTERIAL**

V ≤ 60 KM/H

**1. EXAMPLE SHOWN:**

Two-way - four lane collector or arterial road.

**2. CONDITIONS:**

Work duration: 30 minutes or less. For longer duration work, use single lane closure example (Drawing No. 3.2 or 3.3).

Speed limit: 60 km/h or lower.



**3. NOTES:**

Flashing arrow board must be activated to alert traffic of work ahead.

**4. SET-UP PROCEDURE:**


Activate flashing arrow board to alert traffic of work ahead.

Commence work.



			<b>THE CITY OF RED DEER</b>	<b>ENGINEERING DEPARTMENT</b>	
			DRAWN BY: G.B.	TEMPORARY TRAFFIC CONTROL MANUAL	APPROVED BY:
			DATE: JAN. 2025	MOBILE OPERATIONS ON COLLECTOR OR ARTERIAL	ENGINEER
			SCALE: N.T.S.	V ≤ 60 KM/H	DRAWING NO. <b>9.4</b>
NO.	DATE	REVISION			

## 9.5 Mobile Operations on Arterial $V \geq 70 \text{ km/h}$



			THE CITY OF RED DEER      ENGINEERING DEPARTMENT	
DRAWN BY:	G.B.		TEMPORARY TRAFFIC CONTROL MANUAL	APPROVED BY:
DATE:	JAN. 2025		MOBILE OPERATIONS ON ARTERIAL	ENGINEER
SCALE:	N.T.S.		V $\geq$ 70 KM/H	DRAWING NO.
NO.	DATE	REVISION		9.5

## References

The City of Calgary. (2021). *Temporary traffic control manual* (2021 ed.).

The City of Red Deer. (2004). *Public works temporary traffic control manual*.

The City of Red Deer. (2010). *Public works temporary traffic control manual* (Version 2).

Transportation Association of Canada. (2021). *Manual of uniform traffic control devices for Canada* (6th ed.).